

AMENDMENT TO CLAIMS:

1. (Previously amended) A mounting system for a pellicle comprising:

a mounting structure for coupling a pellicle to a mask, wherein a sealed interior portion is formed between the pellicle, the mask and the mounting structure; and

a port on the mounting structure through which a pressure difference can be created between the interior portion and an exterior environment;

a pressure regulator in communication with the port to control a pressure in the interior portion; and

a velocity sensor to determine the velocity of the pellicle, wherein the pressure difference is controlled by the pressure regulator to maintain a flat surface on the pellicle based on a reading from the velocity sensor.

2. (Cancelled).

3. (Previously amended) The mounting system of claim 1, further comprising a source of high pressure gas coupled to the pressure regulator, and a source of low pressure gas coupled to the pressure regulator.

4. (Original) The mounting system of claim 3, wherein one of the sources of pressure gas is the exterior environment.

4
5. (Previously amended) The mounting system of claim 1, further comprising a pressure sensor
operatively coupled to the pressure regulator for detecting a pressure of the interior portion.

5
6. (Previously amended) The mounting system of claim 1, further comprising a position sensor to
determine the position of the pellicle;

wherein the pressure difference is controlled by the pressure regulator to maintain a flat
surface on the pellicle based on a reading from the position sensor.

7. (Cancelled).

6
8. (Original) The mounting system of claim 1, further comprising a calibrated leak from the
interior portion to the exterior environment.

9. (Cancelled).

10. (Cancelled).

7
11. (Original) The mounting system of claim 1, further comprising an aerodynamic fairing
adjacent the mounting structure.

12. (Cancelled)

13. (Cancelled)

14. (Cancelled)

15. (Cancelled)

16. (Cancelled)

17. (Cancelled)

8
18. (Previously amended) A method of reducing distortion of a sealed pellicle for a mask, the pellicle being sealed to the mask to form an interior portion therebetween, the method comprising the steps of:

determining a velocity of the pellicle using a velocity sensor; and

regulating a pressure in the interior portion to maintain a flat surface on the pellicle based on the velocity.

9 8
19. (Original) The method of claim 18, further comprising the step of providing an aerodynamic fairing adjacent the mask to reduce turbulent airflow across the pellicle.

10
20. (Previously amended) The method of claim 18, wherein the pressure is also regulated according to feedback from at least one of a pressure sensor coupled to the interior portion, and a position sensor for the pellicle.

21. (Cancelled)

22. (Cancelled)

09/683,748

- 4 -

23. (Cancelled)

24. (Cancelled)

09/683,748

- 5 -